

# EU2SYS-96 SERIES

## HEATED DISPLAY SYSTEMS



• **HALO HEAT** ... a controlled, uniform heat source that gently holds and surrounds food for better appearance, taste, and longer holding life.

• Holds and displays hot food fresh and moist for hours — without adding water.

• Expandable system to meet your specific requirements.

### • HOT DISPLAY CASE

- Curved glass styling.
- Displays hot food without condensation on glass.
- Protected with an environmentally friendly bumper, made of 93% pre-consumer polycarbonate waste and is 100% recyclable.
- Tempered sliding glass doors reflect heat back into the products and mirror the display to enhance merchandising effect.
- Holds a full range of standard (gastronorm) pan sizes, full-size or half-size sheet pans.
- Standard stainless steel front and black painted end panels.
- Thermostatically controlled heat source radiates from the base of the display case in multiple heat zones.
- Overhead light zones with shatterproof coated bulbs.

### • DECORATOR BASE

- Designed to accommodate your choice of equipment (750-TH-II, 750-TH-II/D, 750-S, 500-2D) or optional shelf.
- Stainless steel, distinctively framed in black as standard, and brushed stainless or custom color as alternate choices.

### • SELF-SERVICE HOT DISPLAY

- Customer self-service opening is available on right side or left side of case.
- Front mounted heat-guard provides customer protection.



**EU2SYS-96**  
FRONT VIEW SHOWN WITH  
OPTIONAL CASTERS

The display case is constructed of 18 gauge, non-magnetic stainless steel. A curved, tempered glass front encloses the display case and can be lifted to a 90 degree angle for easy cleaning. Removable, sliding glass doors on the operator side are included. Sliding door tracks have a "clean sweep" cutout allowing for easy cleaning and crumb removal. Framed end clear glass with rubber gasket material protects glass edges from chipping and breakage. The base is divided into three (3) individually managed heat zones with each zone controlled by a separate thermostat with a range of 1 through 10 and heat-on indicator light. Overhead lights are controlled by ON/OFF switches in three (3) light zones. Two (2) 125V plug outlets are available as an option on 120/208-240V units only.

**EU2SYS-96\*** - 96" (2438mm) length, with BU2 base

**EU2SYS-96/PL\*** - 96" (2438mm) length, with BU2 base, 23-3/4" (603mm) self-service opening on left side of case front

**EU2SYS-96/PR\*** - 96" (2438mm) length, with BU2 base, 23-3/4" (603mm) self-service opening on right side of case front

\*The system base is not sold as a separate item. Order the full EU2SYS model to receive the base.

### FACTORY INSTALLED OPTIONS

#### • Electrical Choices

- Specify Voltage:
- 120/208-240
  - 230
  - 380-415

#### • Panel Color Choices

- Specify color:
- Black, standard
  - Stainless Steel, optional
  - Custom Color, optional

#### • End Glass Choices

- Specify choice
- Clear Glass, standard
  - Solar Bronze Glass, optional

Temperature Gauge, optional




W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A.

PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA


FAX: 262.251.7067 800.329.8744 U.S.A. ONLY

[www.alto-shaam.com](http://www.alto-shaam.com)





**EU2SYS Profile**



**EU2SYS-96**

<b>DIMENSIONS (H X W X D)</b>	
<b>EXTERIOR, WITH BASE:</b> 58-3/16" x 96" x 44-5/16" (1477mm x 2438mm x 1125mm)	
<b>WELL DIMENSIONS (W X L X D):</b> 27-3/16" x 93-5/16" x 4-1/2" (690mm x 2370mm x 114mm)	

<b>ELECTRICAL</b>					
VOLTAGE	PHASE	CYCLE/HZ	AMPS	kW	
120/208-240 (AGCY)	1	50/60	24.0	5.2	BARE END, NO PLUG
	1	50/60	24.0	5.2	
	1	50/60	24.0	5.2	
230 (AGCY)	1	50	24.9	5.7	BARE END, NO PLUG
	1	50	24.3	5.6	
380-415 (AGCY)	3	50	10.7	6.5	BARE END, NO PLUG
	3	50	9.7	5.2	
	3	50	10.3	6.2	

<b>PAN CONFIGURATION*</b>		
PAN SIZE	DIMENSIONS	QTY.
FULL-SIZE & ONE-THIRD**:	12" x 20" x 2-1/2" (GN 1/1)	7
	12" x 6" x 2-1/2" (GN 1/3)	7
HALF-SIZE & ONE-THIRD**:	12" x 10" x 2-1/2" (GN 1/2)	14
	12" x 6" x 2-1/2" (GN 1/3)	7
FULL-SIZE SHEET PANS:	18" x 26" x 1"	4
<b>MAX. CAPACITY/VOLUME:</b>		112 lbs (51 kg) 70 qts (84 L)

\* Pans are not included with display case.  
\*\* Will also accept 4" (100mm) deep pans.

<b>SPECIFICATIONS</b>	
<ul style="list-style-type: none"> <li>• Fourteen (14) overhead lights in three (3) light zones.</li> <li>• Three (3) base heat zones with three (3) adjustable thermostats with a range of 1 through 10, and three (3) heat-on indicator lights.</li> <li>• Four (4) tinted, reflective, tempered glass sliding doors on operator side.</li> <li>• Two (2) 10" x 36" (254mm x 914mm) operator-side work shelves.</li> <li>• Self-serve models EU2SYS-96/PL and EU2SYS-96/PR have a self-serve pan insert 21-5/8" x 26-7/16" x 2" (549mm x 672mm x 51mm) and includes one (1) Wire Pan Grid.</li> </ul>	

**INSTALLATION REQUIREMENTS**

Display case must be installed level. The display case must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.

Do not install a heated display case near a cold air source such as a freezer, air conditioning vents, or in any area where outside air fluctuation can affect performance.

<b>WEIGHT (EST.)</b>		
MODEL	NET	SHIP
EU2SYS-96	676 lb (307 kg)	735 lb (333 kg)
EU2SYS-96/PL/PR	676 lb (307 kg)	735 lb (333 kg)
<b>CRATED DIMENSIONS: L X W X H</b>		
EU2SYS-96: 45" x 100" x 75" (1143mm x 2540mm x 1905mm)		

<b>FACTORY INSTALLED OPTIONS</b>			
<input type="checkbox"/> INDEPENDENT ELECTRICAL OUTLET	5001781	<input type="checkbox"/> TEMPERATURE PROBE	5004918

<b>ACCESSORIES</b>			
<input type="checkbox"/> CARVING STATION	5001874	<b>SHEET PAN DIVIDER BAR PACKAGE</b>	
<input type="checkbox"/> CASTERS, PLATE (Includes 2 - 5" (127mm), RIGID and 2 - 5" (127mm), SWIVEL WITH BRAKE)	4007	<input type="checkbox"/> FULL-SERVICE	5002805
		<input type="checkbox"/> SELF-SERVICE LEFT-SIDE OR RIGHT-SIDE OF CASES	5002806
<input type="checkbox"/> LOW PROFILE BASE OVERALL HEIGHT REDUCED BY 4-3/4" (121mm)	304352	<input type="checkbox"/> SHELF, STAINLESS STEEL	5005786
		<input type="checkbox"/> THERMOSTAT GUARD COVER PLATE	5007660
<b>PLATFORM SCALE</b>		<input type="checkbox"/> WORK SHELF WITH GRAVY LANE	5005640
<input type="checkbox"/> LEFT-HAND	5001308		
<input type="checkbox"/> RIGHT-HAND	5001307		