



BPW1E

Single Wide Proof Box

STANDARD FEATURES

- Low profile, 94" overall height
- Patented air flow system
- Easy access heat and humidity system
 - Internally mounted
 - No flushing required
- Field reversible door
- Eye-level digital control panel
 - Set heat/humidity system
 - Four independent timers
- Stainless steel interior and exterior
- Modular panel construction with cam lock attachment
- Field assembled – shipped knocked down
- Open floor – no ramp required

OPTIONS & ACCESSORIES

- Pass-Thru
- Stainless steel floor – no ramp required
- Window in door
- Interior light
- Prison package
- Upper side trim – 1 or 2 sides

MODEL CONFIGURATION

- 34.0"D** – (may be shipped assembled)
 - One Single End or Side Load Rack
- 60.5"D**
 - Two Single End or Two Single Side Load Racks
- 80.5"D**
 - Two Single End or Two Single Side Load Racks
- 100.5"D**
 - Three Single End or Three Single Side Load Racks
- 120.5"D**
 - Four Single End or Four Single Side Load Racks



Area Reserved For Consultant & Contractor Approvals



19220 State Route 162 East
Orting, WA 98360
www.baxterbakery.com


Factory
(360) 893-5554

Customer Care
(800) 777-2828
or
(800) 462-2778

Customer Care Fax
(937) 332-2852



BPW1E Single Wide Proof Box



- 74" max. Rack Height
- Door May Be Hinged Left or Right on Site
- Freight Class: 85

Physical Data	Model 34.0"D	Model 60.5"D	Model 80.5"D	Model 100.5" D	Model 120.5"D
Interior Dimensions	74.5" H x 31.25" D x 26.1" W 189.2cm x 79.4cm x 66.3cm	74.5" H x 57.75" D x 26.1" W 189.2cm x 146.7cm x 66.3cm	74.5" H x 77.75" D x 26.1" W 189.2cm x 197.5cm x 66.3cm	74.5" H x 97.75" D x 26.1" W 189.2cm x 248.3cm x 66.3cm	74.5" H x 117.75" D x 26.1" W 189.2cm x 299.1cm x 66.3cm
Exterior Dimensions	99.5" H x 36.75" D x 35.5" W 252.7 x 93.3cm x 90.2cm	99.5" H x 63.25" D x 35.5" W 252.7 x 160.7cm x 90.2cm	99.5" H x 83.25" D x 35.5" W 252.7 x 211.5cm x 90.2cm	99.5" H x 103.25" D x 35.5" W 252.7 x 262.3cm x 90.2cm	99.5" H x 123.25" D x 35.5" W 252.7 x 313.1cm x 90.2cm
Net Door Opening Height	74.5" / 189.2cm	74.5" / 189.2cm	74.5" / 189.2cm	74.5" / 189.2cm	74.5" / 189.2cm
Net Door Opening Width	24.5" / 62.2cm	24.5" / 62.2cm	24.5" / 62.2cm	24.5" / 62.2cm	24.5" / 62.2cm
Power Input with Neutral ^A	208-240V/50-60Hz/1/18.4-20.4A Or 208-240V/50-60Hz/3/18.4-20.4A	208-240V/50-60Hz/1/18.4-20.4A Or 208-240V/50-60Hz/3/18.4-20.4A	208-240V/50-60Hz/1/37.0-42.0A Or 208-240V/50-60Hz/3/32.0-37.0A	208-240V/50-60Hz/1/37.0-42.0A Or 208-240V/50-60Hz/3/32.0-37.0A	208-240V/50-60Hz/1/37.0-42.0A Or 208-240V/50-60Hz/3/32.0-37.0A
KD Shipping Info (crate dims & approx. wgt.)	91.5"D x 36.5"W x 65.5"H 850 lbs. ^B	—	—	—	—

UTILITIES & NOTES

- 1 **Water:** 1/2" FNPT cold water 30-80 psi at 85" (215.9 cm) AFF.
NOTE: Water supply must have the proper hardness, pH & chloride concentration. Consult your local water company and/or water conditioner dealer before installation.
 - **Recommended water hardness range:** 2-4 grains per gallon.
 - **Recommended pH range:** 7.0 to 8.0.
 - **Acceptable range for chloride concentration:** 0-30 ppm.
- 2 **Drain:** 1/2" FNPT, front or rear drain at 5" (12.7 cm) AFF. Rte to air-gap drain
- 3 **Power:** Provide connection(s) at 85" (215.9 cm) AFF. See chart above for specific information.
 - ^A Neutral wire circuitry needed to provide 110-120V for control components. A separate line may be run or a transformer will be required if 110 -120V is not available.

Installation: Floor should be level within 1/8" per foot for proper installation. Slope should not exceed 3/4" in all directions under the unit

- ^B Contact factory for shipping information if shipping assembled.

SHORT SPECIFICATION

The proofer shall be of stainless steel construction, manufactured in the United States by Baxter Mfg. The unit footprint shall be no wider than 35.5" W. Built using modular panel construction with cam lock attachment, the proofer shall incorporate foam insulation and gaskets to form a strong, energy efficient enclosure. Nonmetallic interior bumpers shall protect the interior on all sides.

The proofer shall include eye level, digital controls in the door and a patented air flow system. No ramp is required for this unit. The controls will independently set the temperature and humidity for precise proofing control.

Four individual count-down timers for products with different time requirements shall be provided. The air flow system will include an internally mounted humidifier. No flush cleaning is required. The proofer door shall be field reversible.

The proofer will bear the following agency approvals: UL for safety and sanitation and city of Los Angeles.

Manufacturer reserves the right to make changes in sizes and specifications.



19220 State Route 162 East
Orting, WA 98360
www.baxterbakery.com

Factory
(360) 893-5554

Customer Care
(800) 777-2828
or
(800) 462-2778

Customer Care Fax
(937) 332-2852