


<b>Type:</b>	<b>Issue Date:</b>	<b>Project:</b>
<b>Part #: A19CL40/5</b>		



# INCANDESCENT LAMPS

General Service



Bulb	Base	Product Number	Footnotes	Product Code	Description	Pkg. Qty.	Volts	Lumens	Avg. Life	Design Filament	MOL	Beam Spread
<b>39 WATT</b>												
PAR20	Med.	70343	\$.t,17	HP20NFL39/HX	Narrow Flood HaloXen®	1/15	120	530	2000	CC-8	3.23"	30°
		70354	\$.t,17	HP20NFL39/HX/130	Narrow Flood HaloXen®	1/15	130	530	2000	CC-8	3.23"	30°
PAR30	Med.	70347	\$.t,17	HP30FL39/HX	Flood HaloXen®	1/15	120	530	2000	CC-8	3.62"	30°
		70353	\$.t,17	HP30FL39/HX/130	Flood HaloXen®	1/15	130	530	2000	CC-8	3.62"	30°
PAR30L	Med.	70344	\$.t,17	HP30FL39L/HX	Flood HaloXen®	1/15	120	530	2000	CC-8	4.75"	36°
		70204	\$.t,17	HP30WFL39L/HX	Wide Flood HaloXen®	1/15	120	530	2000	CC-8	4.75"	50°
		70203	\$.t,17	HP30SP39L/HX	Spot HaloXen®	1/15	120	530	2000	CC-8	4.75"	15°
		70356	\$.t,17	HP30FL39L/HX/130	Flood HaloXen®	1/15	130	530	2000	CC-8	4.75"	36°
PAR38	Med.	70340	\$.t,17	HP38FL39/HX	Flood HaloXen®	1/15	120	530	2000	CC-8	5.31"	30°
		70404	\$.t,17	HP38SP39/HX	Spot HaloXen®	1/15	120	530	2000	CC-8	5.31"	10°
		70355	\$.t,17	HP38FL39/HX/130	Flood HaloXen®	1/15	130	530	2000	CC-8	5.31"	30°
<b>40 WATT</b>												
A15	Cand.	10005		A15CL40/E12	Clear	20/120	120	350	2000	C-9	3.50"	-
		10006	X	A15WH40/E12	White	20/120	120	310	2000	C-9	3.50"	-
	Int.	10009	X	A15CL40/E17	Clear	20/120	120	350	2000	C-9	3.50"	-
		Med.	6017		A15CL40	Clear	20/120	130	300	3000	C-9	3.50"
	90300			A15CL40/CSTF	Clear CoverShield® PFA	20/120	130	300	3000	C-9	3.50"	-
	6018			A15FR40	Frost	20/120	130	290	3000	C-9	3.50"	-
A19	Med.	103710	L, AI	A19CL40	Clear	120	130	340	1500	C-9	4.25"	-
		6324		A19CL40/5	Clear	120	130	320	5000	C-9	4.25"	-
		103702	L, AI	A19FR40	Frost	120	130	325	1500	C-9	4.25"	-
		6320		A19FR40/5	Frost	120	130	275	5000	C-9	4.25"	-
		6220		A19SW40/120	Soft White	120	120	300	1500	CC-6	4.25"	-
		8013		A19BG40	Yellow Bug	20/120	130	-	2000	C-9	4.25"	-
		101151	X	A19BLU40T	Transparent Blue	12/120	130	-	2000	C-9	4.25"	-
		101153	X	A19GRN40T	Transparent Green	12/120	130	-	2000	C-9	4.25"	-
		101155		A19RED40T	Transparent Red	12/120	130	-	2000	C-9	4.25"	-
		101125		A19RS40/CS	CoverShield®	20/120	130	-	2000	C-9	4.25"	-
		6354	X	A19YEL40C	Ceramic Yellow	12/120	130	-	2000	C-9	4.25"	-
A21	Med.	20002		A21ANT40	Antique Oil-Rubbed finish	6/48	120	130	3000	Quad Loop	5.00"	-
R14	Int.	9101		R14INT40	Flood	25/250	130	260	1500	CC-2V	2.64"	-
	Med.	9100		R14MED40	Flood	25/250	130	260	1500	CC-2V	2.64"	-
R16	Med.	9127		R16MED40	Flood	25/500	130	235	3000	C-9	3.66"	-
		129127		R16MED40/120	Flood	25/500	120	235	3000	C-9	3.66"	-
		104106		R16SP40	Spot	25/500	130	235	3000	CC-2V	3.66"	-

140 ■ TOC © Means this lamp meets Federal Minimum Efficiency standards. Incandescent lamp symbols, footnotes and abbreviations are located on pages 151-153.