


Type:	Issue Date:	Project:
Part #: A19RS100/CS		



INCANDESCENT LAMPS

General Service



Bulb	Base	Product Number	Footnotes	Product Code	Description	Pkg. Qty.	Volts	Lumens	Avg. Life	Design Filament	MOL	Beam Spread
70 WATT												
PAR38	Med.	70346	Ⓢ,17	HP38FL70/S/HX	Silver PAR Flood HaloXen®	1/15	120	1350	1500	CC-8	5.31"	30°
		70352	Ⓢ,17	HP38SP70/S/HX	Silver PAR Spot HaloXen®	1/15	120	1350	1500	CC-8	5.31"	10°
72 WATT												
A19	Med.	76000	Ⓢ	A19CL72/H	Clear	12/120	120	1490	1000	CC-8	4.25"	-
		76003	Ⓢ	A19SW72/H	Soft White	12/120	120	1490	1000	CC-8	4.25"	-
75 WATT												
A19	Med.	103714	L, AI	A19CL75	Clear	120	130	860	1500	C-9	4.25"	-
		6326	L	A19CL75/5	Clear	120	130	700	5000	C-9	4.25"	-
		103706	L, AI	A19FR75	Frost	120	130	820	1500	C-9	4.25"	-
		6322	L	A19FR75/5	Frost	120	130	680	5000	C-9	4.25"	-
		6222	L	A19SW75/120	Soft White	120	120	780	1500	CC-6	4.25"	-
		6152		A19RS75	Rough Service	20/120	130	1100	2500	C-9	4.25"	-
		6142		A19RS75/CS	CoverShield®	20/120	130	-	2000	C-9	4.25"	-
		A21	Med.	101248	N	A21FR75/ND	Frost Neodymium PureLite®	12/60	120	710	5000	CC-6
80 WATT												
PAR38	Med.	70351	Ⓢ,17	HP38FL80/S/HX	Silver PAR Flood HaloXen®	1/15	120	1680	1500	CC-8	5.31"	30°
100 WATT												
A19	Med.	6327	L	A19CL100/5	Clear	120	130	1000	5000	C-9	4.25"	-
		101182	3,8	A19CL100/SB	Clear Silver Bowl Prism®	12/120	130	830	5000	C-9	4.25"	-
		6323	L	A19FR100/5	Frost	120	130	980	5000	C-9	4.25"	-
		103028	L	A19FR100/P10	Frost Prism® Ultra Life®	20/120	120	870	10000	C-9M	4.25"	-
		6223	X	A19SW100/120	Soft White	120	120	1050	1500	CC-6	4.25"	-
		6153		A19RS100	Rough Service	20/120	130	1150	2500	C-9	4.25"	-
		6143		A19RS100/CS	CoverShield®	20/120	130	-	2500	C-9	4.25"	-
A21	Med.	101246	N	A21CL100/ND	Clear Neodymium PureLite®	12/60	120	1050	5000	CC-6	5.00"	-
		103576	X	A21FR100/P5	Frost Prism® Long Life Plus™	12/60	130	1050	5000	C-9M	5.00"	-
		101197	N	A21FR100/ND	Frost Neodymium PureLite®	12/60	120	1050	5000	CC-6	5.00"	-
		101190	3,8	A21FR100/SB	Inside Frost Silver Bowl Prism®	12/60	130	800	5000	C-9	5.00"	-
		6041		A21RS100/P5/CS	CoverShield® Prism®	12/60	130	-	5000	C-9M	5.00"	-

Ⓢ Means this lamp meets Federal Minimum Efficiency standards.
Incandescent lamp symbols, footnotes and abbreviations are located on pages 151-153.