




BCX-14E & BCX-14G COMBI

with Standard Control

DAILY CLEANING



STEP 1 Open the oven door. Place the oven in cool down mode. Let the oven cool to below 140°F (60°C).




STEP 2 Fill the spray bottle with a mild oven detergent. We recommend the following cleaners: *Greasecutter Plus* by Ecolab, *EZ Clean* by Cello, or *Advance Oven Cleaner* by Diversey-Lever. **DO NOT USE ABRASIVE CLEANERS ON YOUR BLODGETT COMBI.** Be sure to read and follow the MSDS or safety instructions on the bottle of your oven cleaner.



STEP 3 Pump the bottle twenty times to build up pressure. The higher the pressure, the finer the spray.



STEP 4 Spray the oven interior. Turn the nozzle to adjust the spray pattern.



STEP 5 Close the door. Place the oven in steam mode for 10 minutes.



STEP 6 When finished steaming, open the door and rinse the interior with the attached spray hose.



STEP 7 Leave the door open overnight to vent the oven. If the oven will not be used for an extended period of time, place the oven in hot air mode to dry.



DELMING

Deliming the steam generator is the single most important preventative maintenance task. Lime will build up inside the steam generator, reducing efficiency and causing damage to the boiler.

NOTE: Once the deliming process has been started, the oven cannot be used until deliming is complete, approximately 45 minutes.



STEP 1 When it is time to delime your BCX, the delime indicator light at the bottom of the control panel flashes. **This is a warning only, the oven can be used all day with the light on.**



STEP 2 The boiler should be warm to delime. If the oven is hot, place in the cool down mode with the door open until the cavity is below 140°F (60°C).
If the boiler is cold, place the oven in the steam mode for approximately 10 minutes.




STEP 3 Fill the deliming fluid container. Use a non-diluted deliming agent such as *Lime Away* by Eco-Labs or *Lime Out* by US Chemical. **Be sure to read and follow the MSDS or safety instructions on the bottle of your deliming agent.**



STEP 4 If you heated the boiler in step 2, open the oven door and place the oven in cool down mode.



STEP 5 Press and release the steam on demand button. The delime lamp flashes faster.



STEP 6 With the oven door open, turn the oven to the OFF mode. The remainder of the process is automatic. The delime lamp stays lit until deliming is completed.



STEP 7 When the delime lamp goes out, the oven can be used normally.