


Type:	Issue Date:	Project:
Part #: F8T5CW		



## LINEAR FLUORESCENT LAMPS



Bulb	Watts	Product Number	Footnotes	Product Code	Description	Pkg. Qty.	Color Temp.	CRI	Initial Lumens	Mean Lumens	Avg. Life	Nom. Length
<b>ProLume. Preheat - Miniature Bi-Pin</b>												
T5	4	9213	1,7	F4T5CW	Cool White	10/1000	4100	65	130	117	6000	6"
	6	9200	1,7	F6T5CW	Cool White	10/500	4100	65	240	216	6000	9"
	8	9206	1,7	F8T5BLB	Blacklight-Blue	10/500	-	-	-	-	6000	12"
	8	9201	1,7	F8T5CW	Cool White	10/500	4100	65	350	315	6000	12"
	8	9215	1,7	F8T5DL	Daylight	10/500	6500	75	350	279	6000	12"
	8	9210	1,7	F8T5WW	Warm White	10/500	3000	63	400	380	6000	12"
	13	9231	1,7	F13T5CW	Cool White	10/200	4100	65	740	666	6000	21"
	13	9232	1,7	F13T5WW	Warm White	10/200	3000	63	870	825	6000	21"
	<b>ProLume. Preheat - Medium Bi-Pin</b>											
T8	14	109370	1	F14T8CW	Cool White	25	4100	62	650	585	8000	14"
	15	9202	1	F15T8CW	Cool White	30	4100	62	770	690	8000	17"
	15	109212	1	F15T8DL	Daylight	30	6500	74	770	690	8000	17"
	15	109208	1	F15T8WW	Warm White	30	3000	63	845	750	8000	17"
	30	9225	1	F30T8CW	Cool White	30	4100	62	2100	1900	9000	35"
T12	14	9228	1	F14T12CW	Cool White	30	4100	62	480	432	9000	14"
	15	9212	1	F15T12CW	Cool White	30	4100	62	650	570	9000	17"
	20	9203	1	F20T12CW	Cool White	30	4100	62	1150	1000	8000	24"
	20	9235	1	F20T12DL	Daylight	30	6500	74	1100	960	8000	24"
	20	9227	1	F20T12WW	Warm White	30	3000	62	1200	1080	8000	24"
<b>ProLume. T-5 Programmed Start - Miniature Bi-Pin Eco-Shield.</b>												
T5	14	30117	1,7	F14T5/830/ECO/IC	830 Phosphor	25	3000	86	1350	1270	24000	22"
	14	30118	1,7	F14T5/835/ECO/IC	835 Phosphor	25	3500	86	1350	1270	24000	22"
	14	30119	1,7	F14T5/841/ECO/IC	841 Phosphor	25	4100	86	1350	1270	24000	22"
	21	30125	1,7	F21T5/830/ECO/IC	830 Phosphor	25	3000	86	2100	1990	24000	34"
	21	30126	1,7	F21T5/835/ECO/IC	835 Phosphor	25	3500	86	2100	1990	24000	34"
	21	30127	1,7	F21T5/841/ECO/IC	841 Phosphor	25	4100	86	2100	1990	24000	34"
	24	30134	1,7	F24T5/835/HO/ECO/IC	835 Phosphor High Output	25	3500	86	2000	1900	20000	22"
	24	30135	1,7	F24T5/841/HO/ECO/IC	841 Phosphor High Output	25	4100	86	2000	1900	20000	22"
	28	35041	1,7	F28T5/830/ECO/IC	830 Phosphor	25	3000	86	2900	2750	24000	46"
	28	35042	1,7	F28T5/835/ECO/IC	835 Phosphor	25	3500	86	2900	2750	24000	46"
	28	35046	1,7	F28T5/835/ECO/XL	835 Phosphor	25	3500	86	2800	2660	40000	46"
	28	35043	1,7	F28T5/841/ECO/IC	841 Phosphor	25	4100	86	2900	2750	24000	46"
	28	90016	1,7	F28T5/841/ECO/IC/CS	841 Phosphor, CoverShield®	25	4100	86	2900	2750	24000	46"
	28	35044	1,7	F28T5/850/ECO/IC	850 Phosphor	25	5000	86	2900	2750	24000	46"

Ⓢ Means this lamp meets Federal Minimum Efficiency standards.  
Linear Fluorescent lamp symbols, footnotes and abbreviations are located on pages 90-91.