



Item # \_\_\_\_\_

We put space to work.

Job \_\_\_\_\_

## MetroMax® Q Polymer/Wire Shelving Starter and Add-on Units.

Quick-to-adjust, corrosion resistant shelving constructed of removable polymer open grid shelf mats, wire shelf frames, and corner releases. Shelf frames and steel posts have an epoxy coating over an electroplated substrate. Shelves and epoxy coated posts offer a 15 year warranty against rust and corrosion. Shelf mats and posts have built-in Microban® antimicrobial product protection. Rigid four-sided shelf frame and welded corners provide complete 360° capture of the wedge and post to ensure stability, strength and structural integrity. Each Starter and Add-on unit has a maximum capacity of 2,000 lbs. (907kg) evenly distributed. Units assemble easily — Shelves mount on four one-piece wedges along grooved, numbered posts. Shelves adjust on 1" (25mm) increments.

- **Starter units:** shelves and posts under one easy to order model number.
- **Add-on units:** include (2) posts, open grid mat shelves, and S-hooks to connect a unit end-to-end under one easy to order model number.
- **Corner (Right Angle) units:** allow easy access to the shelf contents by eliminating a front post. They are configured using a starter unit, an add-on unit and intermediate "S" hook brackets.
- **Forever Strong:** Proven corner connection and four-sided shelf frame with center truss(es) assures stability and strength in stationary, mobile, and high-density track shelving configurations. 800 lbs. (363kg) per shelf for lengths of 24" to 48" (610 to 1219mm) 600 lbs. (272kg) per shelf for lengths of 54" (1372mm) or longer Stationary unit: 2000lbs (907kg) evenly distributed.
- **Rust & Corrosion Resistant:** Shelves and posts offer a 15 year warranty against rust and corrosion.
- **Easy to Clean and Maintain:** Polymer mats can be easily removed and cleaned in a sink or commercial washer / dish machine.
- **Microban® Antimicrobial Product Protection:** is built into the shelf mats and posts to inhibit the growth of bacteria, mold, mildew, and fungus that cause odors and product degradation. Microban product protection keeps the product "cleaner between cleanings".
- **Quick-to-Adjust:** Patented corner release allows shelves to be adjusted without tools. Simply flip each corner release, relocate the wedge connectors on the posts, and reposition the shelf. Quickly adjust shelves to reclaim wasted vertical space.
- **Efficient Use of Space:** Shelves adjust on 1" (25mm) increments along the post to maximize the use of available vertical space.
- **Fast, Easy Assembly:** Shelves are ready to use right out of the box. One-piece wedges securely attach to the posts – Raised beads on the back of each wedge snap into the grooves on the post. Window on wedge aligns with numbers on the post to locate the desired shelf position. Shelf seats into position over the posts and wedges. A unit can be assembled without tools in minutes.
- **Open Grid (vented) Shelf mats:** Sectioned and promote air circulation and light penetration. Built-in ship's edge helps contain supplies.
- **NSF Listed for all environments.**
- **Maximum Versatility:** Complete line of accessories are found on spec sheet 9.25.



Four Tier Starter Unit



Starter Unit

Add-on Unit

Supports good  
**HACCP**  
processes

MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban® Products Company, Huntersville, NC. Microban® product protection does not by itself protect a user from food borne illness. Product must be routinely cleaned.

L02-202 Printed in U.S.A. 12/17



**InterMetro Industries Corporation**  
North Washington Street, Wilkes-Barre, PA 18705  
Product Information. U.S. and Canada: 1.800.992.1776  
Outside U.S. and Canada: www.metro.com/contactus

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2017 InterMetro Industries Corp.



**MetroMax® Q** Polymer/Wire Shelving Starter and Add-on Units

**9-11**




# MetroMax® Q Starter & Add-on Units

We put space to work.®



## Material Specifications:

- Shelf Mats: Injection-molded polypropylene with exclusive built-in Microban® antimicrobial product protection.
- Shelf frames and epoxy-coated posts: Steel with electroplated substrate and highly durable, abrasion-resistant epoxy finish. The adjustable foot is reinforced nylon.
- Epoxy Coated Posts: Steel with electroplated substrate and highly durable, abrasion-resistant epoxy finish. Epoxy finish has built-in Microban antimicrobial product protection.
- Shelf Wedge Connector: Reinforced nylon.
- Temperature range: -20°F (-29°C) to 125°F (52°C) continuous use, with intermittent exposure to 200°F (93°C) for cleaning.
- Visit metro.com/service-support for cleaning guidelines.



**Starter Units:** consist of four or five open grid shelves and four posts.

**Add-on Units:** consist of four or five shelves, (2) posts, and standard S-Hook Kits (2 per shelf) to configure end-to-end units.  
Four tier units include (8) standard "S" Hooks.  
Five tier units include (10) standard "S" Hooks.



**Corner (Right Angle) Configurations:** select one add-on unit and intermediate "S" Hook

				4-Tier Unit with 63" posts			5-Tier Unit with 74" posts						
Nominal Width/Length (in.)	Nominal Width/Length (mm)	Approx. Pkd. Wt. (lbs.)	Approx. Pkd. Wt. (kg)	Cat. No. Starter Unit	Approx. Pkd. Wt. (lbs.)	Approx. Pkd. Wt. (kg)	Cat. No. Add-On Unit	Approx. Pkd. Wt. (lbs.)	Approx. Pkd. Wt. (kg)	Cat. No. Starter Unit	Approx. Pkd. Wt. (lbs.)	Approx. Pkd. Wt. (kg)	Cat. No. Add-On Unit
18x24	457x610	41.5	18.8	Q316G3	32.5	14.7	AQ316G3	50.4	22.9	5Q317G3	40.4	18.3	5AQ317G3
18x30	457x760	47.5	21.5	Q326G3	34.5	15.6	AQ326G3	57.9	26.3	5Q327G3	47.9	21.7	5AQ327G3
18x36	457x914	53.5	24.3	Q336G3	40.5	18.4	AQ336G3	65.4	29.7	5Q337G3	55.4	25.1	5AQ337G3
18x42	457x1060	59.5	27.0	Q346G3	46.5	21.1	AQ346G3	72.9	33.1	5Q347G3	62.9	28.5	5AQ347G3
18x48	457x1219	65.5	29.7	Q356G3	65.2	29.6	AQ356G3	80.4	36.5	5Q357G3	70.4	31.9	5AQ357G3
18x60	457x1524	53.5	24.3	Q366G3	64.5	29.3	AQ366G3	95.4	43.3	5Q367G3	85.4	38.7	5AQ367G3
18x72	457x1829	89.5	40.6	Q376G3	86.5	39.2	AQ376G3	110.4	50.1	5Q377G3	100.4	45.5	5AQ377G3
21x24	530x610	46.3	21.0	Q416G3	34.3	15.6	AQ416G3	56.4	25.6	5Q417G3	46.4	21.0	5AQ417G3
21x30	530x760	52.3	23.7	Q426G3	39.3	17.8	AQ426G3	63.1	28.6	5Q427G3	53.1	24.1	5AQ427G3
21x36	530x914	57.9	26.3	Q436G3	44.9	20.4	AQ436G3	70.9	32.2	5Q437G3	60.9	27.6	5AQ437G3
21x42	530x1060	67.1	30.4	Q446G3	54.1	24.5	AQ446G3	82.1	37.2	5Q447G3	72.1	32.7	5AQ447G3
21x48	530x1219	72.7	33.0	Q456G3	59.7	27.1	AQ456G3	89.4	40.5	5Q457G3	79.4	36.0	5AQ457G3
21x60	530x1524	86.3	39.1	Q466G3	73.3	33.2	AQ466G3	106.4	48.3	5Q467G3	96.4	43.7	5AQ467G3
21x72	530x1829	98.3	44.6	Q476G3	85.3	38.7	AQ476G3	121.4	55.1	5Q477G3	111.4	50.5	5AQ477G3
24x24	610x610	49.5	22.5	Q516G3	36.5	16.6	AQ516G3	56.4	25.6	5Q517G3	46.4	21.0	5AQ517G3
24x30	610x760	57.5	26.1	Q526G3	44.5	20.2	AQ526G3	66.4	30.1	5Q527G3	56.4	25.6	5AQ527G3
24x36	610x914	65.5	29.7	Q536G3	52.5	23.8	AQ536G3	76.4	34.7	5Q537G3	65.4	29.7	5AQ537G3
24x42	610x1060	73.5	33.3	Q546G3	60.5	27.4	AQ546G3	86.4	39.2	5Q547G3	78.4	35.6	5AQ547G3
24x48	610x1219	81.5	37.0	Q556G3	68.5	31.1	AQ556G3	96.4	43.7	5Q557G3	86.4	39.2	5AQ557G3
24x60	610x1524	77.5	35.2	Q566G3	84.5	38.3	AQ566G3	116.4	52.8	5Q567G3	106.4	48.3	5AQ567G3
24x72	610x1829	113.5	51.5	Q576G3	100.5	45.6	AQ576G3	136.4	61.9	5Q577G3	126.4	57.3	5AQ577G3

**Actual Dimensions:**  
Width: Add 3/8" (10mm) to nominal size. Length: Subtract 3/16" (5mm) from nominal size.



"S" Hook  
Cat. No. M9995



Intermediate "S" Hook Kit  
Cat. No. Q9995Z

Creating a Right Angle (Corner) configuration. Use one standard "S" Hook (included with the Add-on unit) and one Intermediate "S" Hook per tier. Intermediate "S" Hook Bracket

an Ali Group Company



The Spirit of Excellence