# COMBINATION PROCESSOR: Bowl cutter & Vegetable prep robot @ coupe°

## R 301



## SALES FEATURES

**R 301 Combination Processor:** Bowl cutter & Vegetable Prep equipped with a cutter attachment for chopping, fine mincing, emulsions, grinding and kneading, and a vegetable preparation attachment for slicing, grating, ripple cut slicing, and julienne.

#### TECHNICAL FEATURES

R 301 Combination Processor: Bowl cutter & Vegetable Prep. Single phase 120/60/1. Power 1.5 HP. Speed: 1725 rpm. 3.7 L cutter bowl in composite material and smooth bowl-base blade assembly. Vegetable preparation attachment in composite material with side ejection equipped with 2 hoppers: 1 large and 1 cylindrical hopper. Supplied with 2 mm (5/64") grating and 4 mm (5/32") slicing discs. Large range of 23 stainless steel discs available as option. 10 to 80 meals.

Select your options at the back page, F part.

C TEC	HNICAL DATA
Output power	1.5 HP
Electrical data	120V/60/1 - 9 Amp
Speed	1725 rpm
Dimensions (WxDxH)	13 1/16″x11 15/16″x21 1/2″
Rate of recyclability	95%
Net weight	34 lbs
Nema #	5-15P
Reference	R 301 120V/60/1

D Number of meals per service	10 to 80
Quantity per batch in cutter function	Up to 3.3 lbs
Vegetable slicer output	Up to 110 lbs/h

#### VEGETABLE PREPARATION FUNCTION

## **MOTOR BASE**

- Direct drive induction motor (no belt) for intensive use.
- Power1.5 HP
- Stainless steel motor shaft.
- Built in on / off / pulse buttons.
- Magnetic safety and motor brake.
- **Speed**: 1725 rpm.
- Pulse button for better cut precision.

## CUTTER FUNCTION

• 3.7 L cutter bowl with handle, and high resistance smooth blade assembly.

#### **VEGETABLE FUNCTION**

- Vegetable preparation attachment equipped with 2 hoppers:
  - 1 large hopper (surface : 12 square inches) and 1 cylindrical hopper ( $\emptyset$  : 2 1/4"). Removable chute and feed lead.
- Removable chute and feed lead for dishwasher safe and easy cleaning.
- Side ejection for space saving and better user comfort to receive 5 7/8" high GN containers.
- Automatic restart of the machine by the pusher.
- Vertical pusher presses on vegetables for uniform cuts.
- Large range of 23 stainless steel discs available as option.

#### COULIS/ FRUIT SAUCE & CITRUS PRESS FUNCTIONS:

 Option: Juice Extractor Kit including a coulis/ fruit sauce attachment and a citrus press attachment to prepare amusebouche, in-a-glass preparations, sauces, soups, sorbets and ice cream, smoothies, jam, fruit pastes...

### **ACCESSORIES INCLUDED**

- Cutter attachment: lid and high resistance stainless steel smooth blade assembly with removable cap.
- Vegetable attachment: chute, feed lead ejecting disc and discharge plate.
- Supplied with 2 mm (5/64") grating and 4 mm (5/32") slicing discs

#### **STANDARDS**

ETL electrical and sanitation Listed/cETL (Canada)



Update: April 2021

Specification sheet

info@robotcoupeusa.com

## R 301

## F OPTIONAL ACCESSORIES

## BLADE OPTIONS

- Coarse serrated blade assembly for kneading and grinding, ref 27288
- Fine serrated blade assembly for chopping herbs and spices, ref 27287

## OTHER OPTIONS

- Juice Extractor Kit for fruit sauces and citrus fruit juice, ref 27396
- Wall-mounted blade and disc holder: holds 1 blade and 8 discs, ref 107810
- Dice cleaning kit, ref 39881

	SUGGESTED PACKS OF DISCS	
3 disc package	6mm (1/4") coarse grating, 6mm (1/4"×1/4") julienne and 1mm (1/32") slicing discs.	
5 disc package	6mm (1/4") coarse grating, 6mm (1/4"x1/4") julienne and 1mm (1/32") slicing, 2 mm (5/64") julienne and 6 mm (1/4") slicing discs.	

## OPTIONAL DISCS



SLICI	NG
1 mm (1/32")	27051
2 mm (5/64")	27555
3 mm (1/8")	27086
4 mm (5/32")	27566
5 mm (3/16")	27087
6 mm (1/4")	27786



	RIPPLE CUTTING		
2 mm (5/64")		27621	



G	RATING
1.5 mm (1/16")	27588
2 mm (5/64")	27577
3 mm (1/8")	27511
6 mm (1/4")	27046
9 mm (11/32")	27632
Hard Cheese grate	27764
Röstis potatoes	27191
Fine Pulping Disc	27078
Pulping Disc	27079
Pulping Disc	27130



JULIENNE	
2x4 mm (5/64" x 5/32")	27080
2x6 mm (5/64" x 1/4")	27081
2x2 mm (5/64" x 5/64")	27599
4x4 mm (5/32" x 5/32")	27047
6x6 mm (1/4" x 1/4")	27610
8x8 mm (5/16" x 5/16")	27048

ELECTRICAL DATA

120V/60/1 - delivered with cord and plug









