

| Job | Item No. | |
|-----|----------|--|
| | | |

Electric Countertop Hot Plate

Single Spiral Element □H33

Dual Spiral Element □H115 □H63

Dual French Top Element □H70



DESCRIPTION

Wells electric countertop hot plates are designed to be dependable and easy to use. These units are a versatile solution for all sorts of operations, big or small, and take up minimal counter space. These units are a simple way to add reliable cooking power to your kitchen.

SPECIFICATIONS

Wells electric countertop hot plates are constructed with a steel body. H33, H63, and H70 units will come with 4-inch (102 mm) tall plastic legs and H115 units will come with 1-inch (25 mm) tall plastic legs. H33 and H115 units will be 120 V and will come with a factory wired cordset with a 5-15P plug. H63 and H70 models will be 208 V/240 V and will come single phase with no cordset included on standard models, and can be field converted to three phase. The H70 model will also be available as a 220 V/240 V export version. H33, H63, and H115 models will have spiral top[s]. The H70 model will have french tops.

WARRANTY

These units come with a one [1] year warranty for parts and labor.

FEATURES

H33/H115

- Spiral elements are 6 in. (152 mm) in diameter, self-cleaning, and utilize a flat element design for more surface contact.
- Removable chrome-plated drip tray for easy cleaning

H63

- Spiral elements are 8 in. (203 mm) in diameter, self-cleaning, and utilize a flat element design for more surface contact.
- Removable stainless steel drip tray for easy cleaning

H70

• French top elements are 9 in. (229 mm) in diameter to provide very even heat distribution over a large area.

All Models

- Controls have a protective guard ring to prevent accidental temperature changes
- Infinite control switch for precise adjustment of temperature

OPTIONS & ACCESSORIES

- 6-30P cordset for 208 V/240 V models [part number 20141]
- 4-inch (102 mm) tall metal legs [part number 20563]
- 1-inch (25 mm) tall plastic legs [part number 21109]

CERTIFICATIONS









LISTED E6070

LR 10836

STD. 4


¹H70 220 V/240 V model only



Electric Countertop Hot Plate


Single Spiral Element □H33


Dual Spiral Element ☐H115 ☐H63 Dual French Top Element □H70




SPACING ON DUAL ELEMENT MODELS

The distance between burners is 11.5 in. (292 mm) on H115 models and 10.5 in. (267 mm) on H63 and H70 models.







| MODEL | HEIGHT [A] | WIDTH [B] | DEPTH [C] | LEG HEIGHT [D] | APPROX. SHIP WEIGHT | APPROX. WEIGHT INSTALLED |
|-------|---------------|--------------|--------------|----------------------|---------------------------|--------------------------------|
| H33 | 10.1 in. | 12.8 in. | 14.8 | 4 in. | 14 lb. | 11 lb. |
| | (257 mm) | (325 mm) | (376 mm) | (102 mm) | (6.4 kg) | (5 kg) |
| H115 | 7.1 in. | 14.75 in. | 25.7 | 1 in. | 21 lb. | 18 lb. |
| | (180 mm) | (375 mm) | (653 mm) | (25 mm) | (9.5 kg) | (8.2 kg) |
| H63 | 12.6 | 14.75 in. | 25.2 | 4 in. | 30 lb. | 26 lb. |
| | (320 mm) | (375 mm) | (640 mm) | (102 mm) | (13.6 kg) | (11.8 kg) |
| H70 | 12.6 | 14.75 in. | 25.2 | 4 in. | 35 lb. | 32 lb. |
| | (320 mm) | (375 mm) | (640 mm) | (102 mm) | (15.9 kg) | (14.5 kg) |

В

| MODEL | VOLTS | WATTS | 1ф АМРЅ | 3φ [DELTA] AMPS | | | NEMA |
|-------|-------|-------|---------|-----------------|------|------|-------------------|
| MODEL | | | | L1 | L2 | L3 | PLUG |
| H33 | 120 | 1,500 | 12.5 | | | | 5-15P |
| H115 | 120 | 1,650 | 13.8 | | | | 5-15P |
| H63 | 208 | 3,900 | 18.75 | 16.3 | 9.4 | 9.4 | NONE ² |
| | 240 | 5,200 | 21.7 | 18.8 | 10.8 | 10.8 | NOINE- |
| | 208 | 3,000 | 14.4 | 12.5 | 7.2 | 7.2 | |
| H70 | 220 | 3,360 | 15.3 | 13.2 | 7.6 | 7.6 | NONE ³ |
| | 240 | 4,000 | 16.7 | 14.4 | 8.3 | 8.3 | |

CLEARANCES

Allow 1 inch (25 mm) of space between both sides and back of the unit from any combustible surface and 4 inches (102 mm) of space between the bottom of the body of the unit from any combustible surface.

ELECTRICAL CONNECTION LOCATION

[from operator's perspective]

H33—rear of the unit, 0.75 in. (19 mm) from the left and 5.25 in. (133 mm) high H115—rear of the unit, 1 in. (25 mm) from the left and 5.5 in. (140 mm) high

H63 and H70—knockout on rear of the unit, 1.25 in. (32 mm) from the right and 7.25 in. (184 mm) high

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this sheet are subject to change without notice. While Star Manufacturing exercises good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.



² standard version is set up to hardwire, optional version with factory attached cordset available for single phase use

³ set up to hardwire