



Item #: _____ Qty #: _____
Model #: _____
Project #: _____



Brackets Easily Snaps
In On Both Ends

Brackets Are
In A Fixed Position

FEATURES:

Furnished with a 1-5/8" Bullnose edge with a 1-1/4" turn-up edge on sides and rear.

Unit is easily assembled employing the slip-fit TAB-LOK design.

CONSTRUCTION:

Shelf and brackets are die stamped and die formed.

MATERIAL:

WS-KD Series - 18 gauge stainless steel polished to a satin finish.

AWS-KD Series - Heavy gauge aluminum.


SHELF WITH SNAP-IN END BRACKETS

S/S	ALUMINUM	Width	Length	Wt.	Cu.
WS-KD-24	AWS-KD-24	11 1/8"	24"	10 lbs.	1
WS-KD-36	AWS-KD-36	11 1/8"	36"	12 lbs.	1
WS-KD-48	AWS-KD-48	11 1/8"	48"	14 lbs.	1
WS-KD-60	AWS-KD-60	11 1/8"	60"	17 lbs.	1

DETAILS and SPECIFICATIONS

TOL ± .500"

ALL DIMENSIONS ARE TYPICAL



Requirements for NSF Installations

1. Install at least 60" above floor.
2. Limit to dry storage.
3. Avoid contact with liquids.
4. For "Ganging-Up" installation, allow at least 2" between units or mount units side by side and seal joints with an approved sealant.

