

Mobile - Kits

Mobile Post Kits and Shelf Kits with Camguard™ antimicrobial

4 Posts Heights for Mobile Unit (including Casters)

35", 59", 67", 75"

(88,9 cm, 149,9 cm, 170,2 cm, 190,5 cm)

***Note: Post Kits for Mobile Units do not include casters.**

4 Shelf Widths

14", 18", 21", 24"

(35,6 cm, 45,7 cm, 53,3 cm, 61 cm)

5 Shelf Lengths

24", 30", 36", 42", 48"

(61 cm, 76,2 cm, 91,4 cm, 106,7 cm, 121,9 cm.)

• Post Kit for Mobile Units includes:

Two Posts and one each top and bottom Post Connector.

***Note: Casters must be ordered separately.**

• Shelf Kit includes:

Two Traverses and Vented or Solid Shelf Plates to complete one shelf.



Features & Benefits

Versatile Storage

Rolls smoothly into any environment, indoors or outdoors, including walk-in coolers and freezers, dry storage, wet areas or front of the house display. Works in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C). Weldless and rust free. Easy to clean.

Completely Mobile

Choose from Premium or Standard Casters for smooth transporting and for high-density storage needs. Premium casters are made with a zinc plated post and a non-marking polyurethane wheel. Premium Casters can be used in wet areas or in walk-in refrigerators and freezers. Standard casters are chrome plated and can be used for dry storage. Premium Swivel Locking Caster has a locking stem that locks in one direction for rigid positioning. Use four Swivel Locking Casters to create High Density Camshelving systems. The caster controls the direction the unit travels in, eliminating the need for stationary rail tracking. The Premium Total Locking Caster has a brake that locks both the motion and the swivel when set in place. Use two Total Locking Casters and two Swivel Locking Casters for standard Mobile Camshelving Units. **Castors must be ordered separately.**

Easy to Clean

Camshelving shelf plates contain Camguard™ antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing. The traverses and post kits are smooth polypropylene so they can be wiped or steam cleaned. The traverses can be easily removed and washed in a conveyor dishwasher.

Easy to Assemble

Assembles in minutes with the use of a rubber mallet. Requires no bolts or nuts, clips or stainless steel connectors. Molded in dovetails on Posts ensure that Traverses set easily into place.

Item No. _____

Specifier Identification No. _____

Code No. _____


Quantity _____



Mobile Camshelving Unit.




Mobile Post Kit includes two Posts and one each top and bottom Post Connector. (Casters must be ordered separately)




Vented Shelf Kit includes two Traverses and Vented Shelf Set for one shelf.



Solid Shelf Kit includes two Traverses and Solid Shelf Plate Set for one shelf.



Premium Casters.



Standard Casters.

Strong as Steel

Posts and Traverses are made of a steel core coated with polypropylene. Uniquely engineered Post Connectors offer exceptional cross stabilization. Casters are made of reinforced nylon. Maximum weight-bearing capacity of 750 pounds (340 kg) per mobile unit.

Easy to Adjust

Requires use of rubber mallet. Shelves can be adjusted at 4" (10,2 cm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit.

Optional Accessories

Place the 3/2" (8,9 cm) rubber Donut Bumper over the top of the Caster before placing the Caster in the Post. Protects walls and other pieces of equipment from being damaged during mobile unit transport. Identification Tags clip easily onto traverses.

Approvals



Components * Does not include 6" (15 cm) Shelf Plate.

Post Kits for Mobile Units with Posts and Post Connector Set

code	width		height with casters		case lbs. (cube)	case kg. (cube m³)
	in.	cm	in.	cm		
CSPRK1835	18"	45,7	35"	88,9	8.80 (0.32)	3,99 (0,0081)
CSPRK2135	21"	53,3	35"	88,9	9.10 (0.32)	4,13 (0,0081)
CSPRK2435	24"	61,0	35"	88,9	9.50 (0.32)	4,31 (0,0081)
CSPRK1859	18"	45,7	59"	149,9	13.80 (0.41)	6,26 (0,0116)
CSPRK2159	21"	53,3	59"	149,9	14.10 (0.41)	6,40 (0,0116)
CSPRK2459	24"	61,0	59"	149,9	14.50 (0.41)	6,58 (0,0116)
CSPRK1867	18"	45,7	67"	170,2	15.80 (0.46)	7,17 (0,0130)
CSPRK2167	21"	53,3	67"	170,2	16.10 (0.46)	7,30 (0,0130)
CSPRK2467	24"	61,0	67"	170,2	16.50 (0.46)	7,48 (0,0130)
CSPRK1875	18"	45,7	75"	190,5	17.55 (0.52)	7,96 (0,0147)
CSPRK2175	21"	53,3	75"	190,5	17.85 (0.52)	8,10 (0,0147)
CSPRK2475	24"	61,0	75"	190,5	18.25 (0.52)	8,28 (0,0147)

Shelf Kits with Traverses and Vented Shelf Plates

code	width		length		case lbs. (cube)	case kg. (cube m³)
	in.	cm	in.	cm		
24" (61 cm) Traverses						
CS1824VK	18"	45,7	24" 61,0		7.94 (0.83)	3,60 (0,0235)
CS2124VK	21"	53,3	24" 61,0		8.66 (0.83)	3,93 (0,0235)
CS2424VK	24"	61,0	24" 61,0		8.73 (0.83)	3,96 (0,0235)
30" (76,2 cm) Traverses						
CS1830VK	18"	45,7	30" 76,2		9.69 (0.83)	4,40 (0,0235)
CS2130VK	21"	53,3	30" 76,2		10.67 (0.83)	4,84 (0,0235)
CS2430VK	24"	61,0	30" 76,2		10.92 (0.83)	4,95 (0,0235)
36" (91,4 cm) Traverses						
CS1836VK	18"	45,7	36" 91,4		11.44 (0.83)	5,19 (0,0235)
CS2136VK	21"	53,3	36" 91,4		12.68 (0.83)	5,75 (0,0235)
CS2436VK	24"	61,0	36" 91,4		13.11 (0.83)	5,95 (0,0235)
42" (106,7 cm) Traverses						
CS1842VK	18"	45,7	42" 106,7		13.62 (0.97)	6,18 (0,0274)
CS2142VK	21"	53,3	42" 106,7		15.23 (0.97)	6,91 (0,0274)
CS2442VK	24"	61,0	42" 106,7		15.31 (0.97)	6,94 (0,0274)
48" (121,9 cm) Traverses						
CS1848VK	18"	45,7	48" 121,9		14.94 (1.06)	6,78 (0,0300)
CS2148VK	21"	53,3	48" 121,9		16.69 (1.06)	7,57 (0,0300)
CS2448VK	24"	61,0	48" 121,9		17.50 (1.06)	7,94 (0,0300)

Casters

Case Pack: 2 each

code	description	diameter in.	cm	case lbs. (cube)	case kg. (cube m³)
Premium Casters					
CSCSL	Swivel Locking	5"	12,7	6.75 (0.13)	1,53 (0,004)
CSCSL	Total Locking	5"	12,7	11.75 (0.22)	2,67 (0,006)
Standard Casters					
CSSB	Swivel Chrome with Brake	5"	12,7	5.11 (0.15)	2,31 (0,004)
CSCS	Swivel Chrome with no Brake	5"	12,7	4.72 (0.15)	2,14 (0,004)
CSCR	Rigid Chrome	5"	12,7	4.71 (0.15)	2,13 (0,004)

Item No. _____

Specifier Identification No. _____

Code No. _____

Quantity _____

Shelf Kits with Traverses and Solid Shelf Plates

code	width		length		case lbs. (cube)	case kg. (cube m³)
	in.	cm	in.	cm		
24" (61 cm) Traverses						
CS1824SK	18"	45,7	24"	61,0	8.34 (0.83)	3,78 (0,0235)
CS2124SK	21"	53,3	24"	61,0	9.14 (0.83)	4,14 (0,0235)
CS2424SK	24"	61,0	24"	61,0	9.27 (0.83)	4,20 (0,0235)
30" (76,2 cm) Traverses						
CS1830SK	18"	45,7	30"	76,2	10.20 (0.83)	4,63 (0,0235)
CS2130SK	21"	53,3	30"	76,2	11.28 (0.83)	5,12 (0,0235)
CS2430SK	24"	61,0	30"	76,2	11.61 (0.83)	5,27 (0,0235)
36" (91,4 cm) Traverses						
CS1836SK	18"	45,7	36"	91,4	12.06 (0.83)	5,47 (0,0235)
CS2136SK	21"	53,3	36"	91,4	13.42 (0.83)	6,09 (0,0235)
CS2436SK	24"	61,0	36"	91,4	13.95 (0.83)	6,33 (0,0235)
42" (106,7 cm) Traverses						
CS1842SK	18"	45,7	42"	106,7	14.40 (0.97)	6,53 (0,0274)
CS2142SK	21"	53,3	42"	106,7	16.17 (0.97)	7,33 (0,0274)
CS2442SK	24"	61,0	42"	106,7	16.40 (0.97)	7,44 (0,0274)
48" (121,9 cm) Traverses						
CS1848SK	18"	45,7	48"	121,9	15.78 (1.06)	7,16 (0,0300)
CS2148SK	21"	53,3	48"	121,9	17.71 (1.06)	8,03 (0,0300)
CS2448SK	24"	61,0	48"	121,9	18.63 (1.06)	8,45 (0,0300)

Architect Specs

Posts: Internal steel core, reinforced polypropylene exterior.
Post Connectors: Reinforced polypropylene.
Traverses: Internal steel core, reinforced polypropylene exterior.
Vented/Solid Shelf Plates: Reinforced polypropylene with Camguard™ antimicrobial.
Premium Casters: Reinforced nylon with zinc plated post and thermoplastic rubber wheels.
Standard Casters: Chrome plated with rubber wheels.

Optional Accessories

Donut Bumper for Caster ☐ CSRDB **Color:** Dark Gray **Case pack:** 4 each
Identification Tag 6" ☐ CSID **Color:** White/Clear **Case pack:** 12 each
Identification Tag 3" ☐ CSID3 **Color:** White/Clear **Case pack:** 12 each

Standard Color

☐ Speckled Gray (480)

Approvals



Components

* Does not include 6" (15 cm) Shelf Plate.