Printing date 19.02.2016 Revision: 19.02.2016

## 1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Glycol Wick Fuel, Safe Heat
- · CAS Number:

111-46-6

· EC number:

203-872-2

· Index number:

603-140-00-6


- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the preparation Fuel
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Sterno Products

1880 Compton Ave. 101

Corona, CA 92881

Phone: 951-682-9600





ChemTel Inc.

(800)255-3924, +1 (813)248-0585



#### 2 Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



R22: Harmful if swallowed.

- · Information concerning particular hazards for human and environment: Not applicable.
- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS07

· Signal word Warning

(Contd. on page 2)

Printing date 19.02.2016 Revision: 19.02.2016

Trade name: Glycol Wick Fuel, Safe Heat

(Contd. of page 1)

· Hazard-determining components of labelling:

2,2'-oxybisethanol

Hazard statements

H302 Harmful if swallowed.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Wash thoroughly after handling. P264

Do no eat, drink or smoke when using this product. P270

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330 Rinse mouth.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Safety data sheet available on request.

- · Hazard description:
- · WHMIS-symbols:

D1B - Toxic material causing immediate and serious toxic effects



· NFPA ratings (scale 0 - 4)



Health = 2Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



2 Health = 2 1 Fire = 1

· HMIS Long Term Health Hazard Substances

Substance is not listed.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

### 3 Composition/information on ingredients

- · 3.1 Substances
- · CAS No. Description

111-46-6 2,2'-oxybisethanol

(Contd. on page 3)

Printing date 19.02.2016 Revision: 19.02.2016

Trade name: Glycol Wick Fuel, Safe Heat

(Contd. of page 2)

Identification number(s)
EC number: 203-872-2
Index number: 603-140-00-6

#### 4 First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Generally the product does not irritate the skin.

Rinse with warm water.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.

Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Cramp

Nausea

Gastric or intestinal disorders

· Hazards

Danger of convulsion.

Condition may deteriorate with alcohol consumption.

4.3 Indication of any immediate medical attention and special treatment needed

Medical supervision for at least 48 hours.

## 5 Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information Cool endangered receptacles with water spray.

(Contd. on page 4)

Printing date 19.02.2016 Revision: 19.02.2016

Trade name: Glycol Wick Fuel, Safe Heat

(Contd. of page 3)

#### 6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

- · 6.2 Environmental precautions: Prevent from spreading (e.g. by damming-in or oil barriers).
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

· 7.1 Precautions for safe handling

No special precautions are necessary if used correctly.

Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with oxidizing and acidic materials.

Do not store together with alkalis (caustic solutions).

- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · 7.3 Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

#### 111-46-6 2,2'-oxybisethanol

WEEL (USA) 10 mg/m<sup>3</sup>

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

Printing date 19.02.2016 Revision: 19.02.2016

Trade name: Glycol Wick Fuel, Safe Heat

(Contd. of page 4)

Wash hands before breaks and at the end of work.

- Respiratory protection: Not necessary if room is well-ventilated.
   Protection of hands: Not required.
- · Material of gloves Not required.
- · Eye protection:



9 Physical and chemical properties		
9.1 Information on basic physical are General Information	nd chemical properties	
· Appearance: Form:	Finia	
Colour:	Fluid Colourless	
· Odour:	Nearly odourless	
Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	-8,5 °C 245 °C	
· Flash point:	120 °C	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	225 °C	
Decomposition temperature:	Not determined.	
· Self-igniting:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits: Lower: Upper:	0,7 Vol % 22 Vol %	
· Vapour pressure at 20 °C:	0,03 hPa	
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	3,66 g/cm <sup>3</sup> Not determined. Not determined. Not determined.	
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
		(Contd. on page 6)

Printing date 19.02.2016 Revision: 19.02.2016

Trade name: Glycol Wick Fuel, Safe Heat

(Contd. of page 5)

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

• **9.2 Other information**No further relevant information available.

### 10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Reacts with strong acids.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

## 11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values relevant for classification:

#### 111-46-6 2,2'-oxybisethanol

Oral | LD50 | 12565 mg/kg (rat) | Dermal | LD50 | 11890 mg/kg (rabbit)

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Slight irritant effect on eyes.
- · Sensitization: No sensitizing effects known.

## 12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

Printing date 19.02.2016 Revision: 19.02.2016

Trade name: Glycol Wick Fuel, Safe Heat

(Contd. of page 6)

· 12.6 Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· 14.1 UN-Number · DOT, ADR, ADN, IMDG, IATA	N/A	
· 14.2 UN proper shipping name · DOT, ADR, ADN, IMDG, IATA	N/A	
· 14.3 Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA · Class	N/A	
· 14.4 Packing group · DOT, ADR, IMDG, IATA	N/A	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code	x II of  Not applicable.	
· UN "Model Regulation":	-	

### 15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 355 (extremely hazardous substances):

Substance is not listed.

(Contd. on page 8)

Printing date 19.02.2016 Revision: 19.02.2016

Trade name: Glycol Wick Fuel, Safe Heat

(Contd. of page 7)

- Section 313 (Specific toxic chemical listings):

111-46-6 2,2'-oxybisethanol

· TSCA (Toxic Substances Control Act):

Substance is listed.

- · Proposition 65 (California):
- · Chemicals known to cause cancer:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

- · Carcinogenic Categories
- · EPA (Environmental Protection Agency)

Substance is not listed.

· IARC (International Agency for Research on Cancer)

Substance is not listed.

TLV (Threshold Limit Value established by ACGIH)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

- · Canada
- Canadian Domestic Substances List (DSL)

Substance is listed.

Canadian Ingredient Disclosure list (limit 0.1%)

Substance is not listed.

· Canadian Ingredient Disclosure list (limit 1%)

Substance is not listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 9)

Printing date 19.02.2016 Revision: 19.02.2016

Trade name: Glycol Wick Fuel, Safe Heat

(Contd. of page 8)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

· Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com