



SAFETY DATA SHEET

POLYSI® Lubricants

Issued 07/18/19
Revision 0 07/18/19

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: High Performance Lubricant **Product ID#: 048232**
Recommended Use: Lubricant (incidental food contact or not for medical purposes)
Company: PolySi® Technologies
5108 Rex McLeod Drive
Sanford, NC 27330, USA
Telephone: 1-919-775-4989 (PolySi® Technologies)
Emergency Telephone: 1-800-424-9300 (CHEMTREC, 24 hours, Washington, D.C. USA)

2. HAZARDS IDENTIFICATION

Classification: Non-hazardous

Labeling: Symbol:

Signal Word: None

Hazard statements:

May be harmful if swallowed

May cause eye irritation

May cause skin irritation

Non flammable or combustible, but may burn if involved in a fire

Precautionary Statements:

Use personal protective equipment as required. Wear safety glasses and gloves.

3. COMPOSITION / INFORMATION ON INGREDIENTS

White oil and additives

This product contains no hazardous ingredients above reportable thresholds.

4. FIRST AID MEASURES

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. Obtain medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms persist, get medical attention. No need for first aid is anticipated.

Inhalation: If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.

Ingestion: If swallowed, do not induce vomiting. If irritation or discomfort occurs, obtain medical assistance.

5. FIRE FIGHTING MEASURES

Autoignition Temperature: >200°C

Flash point: >200°C

Flammable Limits (LEL) Not determined

Flammable Limits (UEL) Not determined

Suitable Extinguishing Media: On large fires used dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical, or water spray. Water can be used to cool fire exposed containers.



SAFETY DATA SHEET

POLYSI® Lubricants

Issued 07/18/19
Revision 0 07/18/19

Unsuitable Extinguishing Media: None.

Specific hazards in case of fire: Decomposes on heating and produces incompletely burned carbon compounds. Avoid reaction with oxidizers.

Special protective equipment and precautions for fire fighters:

No acute hazard. Move container from fire area, if possible. Avoid breathing vapors or dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a separate escape air supply. Use any self contained breathing apparatus with a full face piece.

Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If safe to do so, remove containers from path of fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use appropriate personal protection. (See section 8.)

Environmental precautions: For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Methods for material containment and cleaning up: Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin, inhalation of mist, or ingestion. See section 8 for personal protection equipment. Practice good personal hygiene to prevent accidental ingestion after handling. Properly dispose of clothing that cannot be decontaminated.

Conditions for safe storage, including any incompatibilities: Store away from oxidizing materials. Store product in a closed container located in a dry area. Do not store in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: Under most handling conditions, this product will not generate mist or dust. US OSHA PEL control parameter for respirable mineral oil is an 8 hour TWA of 5.0 mg/m³.

Engineering Controls: General ventilation recommended.

Personal Protective Equipment (PPE):

Eyes: Safety glasses recommended.

Skin: Impermeable gloves should be worn. Petroleum resistant elastomers are recommended.

Inhalation: No respiratory protection required under most conditions. If concentrations exceed exposure limits, approved respiratory equipment with organic vapor/P100 filter.



SAFETY DATA SHEET

POLYSI® Lubricants

Issued 07/18/19
Revision 0 07/18/19

9. CHEMICAL AND PHYSICAL PROPERTIES

Physical state:	Semi-solid
Color:	Translucent colorless to slight amber
Odor:	Mild petroleum odor
Odor Threshold:	Not available
pH Value:	Not applicable
Melting Point:	Not applicable
Freezing Point:	10°C
Initial Boiling Point:	>200°C
Flash Point:	>200°C COC (Base oil)
Evaporation rate:	Not available
Flammability (solid, gas):	Not applicable
Explosion limits:	Not available
Vapor pressure:	Negligible at 20°C
Vapor density:	Not available
Solubility:	Insoluble in water at 20°C
Partition coefficient:	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Begins to oxidize at a slow rate at 125°C

10. STABILITY AND REACTIVITY

Chemical stability:	Stable under ambient temperatures and pressures
Possibility of hazardous reactions:	Can react with strong oxidizers. Other hazardous reactions have not been identified. Otherwise will not react or polymerize.
Conditions to avoid:	No specific conditions to avoid have been identified.
Materials to avoid:	Oxidizers.
Hazardous decomposition products:	Decomposes on heating and produces incompletely burned carbon compounds.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity: LD50: > 5,000 mg/kg

Species: rat - Information given is based on data obtained from similar substances.

Acute inhalation toxicity (dust/aerosol): LC50: > 5 mg/l; Exposure time: 4 h

Species: rat - Information given is based on data obtained from similar substances

Acute dermal toxicity: LD50: > 2,000 mg/kg

Species: rabbit - Information given is based on data obtained from similar substances

Skin irritation – Prolonged contact may cause redness and irritation

Eye irritation – Contact with eyes may cause irritation

Inhalation – May cause irritation of respiratory tract

Ingestion – Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea

Sensitization – No information available

Carcinogenicity - None of the components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

No information available on reproductive, mutagenic or teratogenic effects.



SAFETY DATA SHEET

POLYSI® Lubricants

Issued 07/18/19
Revision 0 07/18/19

12. ECOLOGICAL INFORMATION

Elimination information (persistence and degradability)

Biodegradability

This material is not expected to be readily biodegradable.

Ecotoxicity

A: General Product Information

No information available for the product

B: Component Analysis

No information available for the product

Persistence/Degradability

This product does not readily degrade.

Bioaccumulation

No information available for the product.

Mobility in Soil

No additional information available.

Environmental Fate

No information available for the product.

13. DISPOSAL PROCEDURES

Waste treatment methods: Waste (substance and container material) shall be recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site. Recycle containers if possible, or dispose of in an authorized landfill.

According to the European Waste Catalogue, Waste Codes are not product specific but application specific. Waste Codes should be assigned by the user based on the application in which the product is used.

For USA Disposal: Waste must be disposed of in accordance with federal, state, and local environmental control regulations.

14. TRANSPORT INFORMATION

Class or Type: US DOT, IMO, ADR, RID, ADN, IMDG, and IATA: Non-hazardous

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the mixture:

Other Information:

U. S. Regulatory information

TSCA Inventory Status:	Y
TSCA 12 (b) Export Notification:	Not listed
CERCLA Section 103 (40 CFR 302.4):	N
SARA Section 302 (40 CFR 355.30):	N
SARA Section 304 (40 CFR 355.40):	N
SARA Section 313 (40 CFR 372.65):	N
OSHA Process Safety (29 CFR 1910.119):	N
SARA Hazard Categories, SARA Sections 311/312 (40 CFR 370.21) -	





SAFETY DATA SHEET

POLYSI® Lubricants

Issued 07/18/19
Revision 0 07/18/19

Acute Hazard:	N
Chronic Hazard:	N
Fire Hazard:	N
Reactivity Hazard:	N
Sudden Release Hazard:	N

State Regulations: This product contains no chemicals at or above reportable levels that are known to the State of California to cause cancer, birth defects, or other reproductive harm.

Chemical Inventories:

DSL (Canada)	All ingredients listed or exempt
EINECS (European Union)	All ingredients listed or exempt
ENCS/ISHL (Japan)	All ingredients listed or exempt
IECSC (Peoples Republic of China)	All ingredients listed or exempt
TSCA (United States of America)	All ingredients listed or exempt

16. OTHER INFORMATION

NFPA Hazard Classification:

Health:	1
Flammability:	1
Reactivity:	0
Special Hazards:	None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification:

Health:	1
Flammability:	1
Reactivity:	0
Protection:	B (See PPE section)

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations.

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

Prepared By: PolySi® Technologies, Inc.
5108 Rex McLeod Dr.
Sanford N.C. 27330

Email polysi@polysi.com
Phone: (919) 775-4989

