

PPC-300WP-II Series

Washdown Portion Control Scales

- IP68 submersible scale in battery mode
- IP65 washdown when using AC adapter
- Checkweighing, grading, fixed, basic weighing, and tare functions
- Pound, kilogram, ounce, pound-ounce



Underside carrying handles

Checkweighing under/accept/over display

Heavy-duty stainless-steel construction with removable platform for easy cleaning

Easy-to-read, 1.2-inch display characters



MODEL	PPC-300WP-II-4.4	PPC-300WP-II-10	PPC-300WP-II-22	PPC-300WP-II-44
Capacity	4.4lb x 0.002lb 80oz x 0.05oz 2kg x 0.001kg 5lb x 0.05oz*	10lb x 0.005lb 160oz x 0.1oz 4kg x 0.002kg 10lb x 0.1oz*	22lb x 0.01lb 352oz x 0.2oz 10kg x 0.005kg 22lb x 0.2oz*	44lb x 0.02lb 704oz x 0.5oz 20kg x 0.01kg 44lb x 0.5oz*
Weighing System	Strain gauge load cell			
Certificate of Conformance	22-002 (US) AM-6204 (Canada)			
Platform	9.1in x 8in (232mm x 202mm), stainless steel, removable			
Display	5-digit, 7-segment LCD			
Character Size	0.5in x 1.2in (13mm x 30mm)			
Power	"D" size batteries (qty. 4) or AC adapter (included)			
Battery Life	3000 hours of continuous use			
Housing Material	Stainless steel			
Operating Temperatures	14°F ~ 104°F (-10°C ~ 40°C)			
Function	Basic weighing, checkweighing, grading, fixed, tare			

*Combined units, such as pound-ounce, are not legal for trade.

Dimensions

